



materials with only one unit.

www.wagner-group.com

Save time & costs!

The mixing and dosing unit WAGNER 2K COMFORT is also available with two fluid circuits that can be applied in parallel.

- Physical separation of the materials avoids unit downtimes especially with highly reactive materials.
- Up to 50% shorter cycle time of the objects compared to the previous model FlexControl Plus.
- Investment cost savings of up to 15% in comparison to an application with two one-circuit units.

Selectable alignment of the fluid cabinets

Optimized positioning depending on available space

Individual solutions

Just as the 2K COMFORT basic version, the two-circuit version can be adapted to specific requirements



Separate operating elements for each fluid circuit

Start, stop, flushing, recipe change
No downtime costs due to operating errors

Flexible operation

Input of parameters & recipes possible via touch display or mobile device

Easy parametrization

The background color of the display indicates clearly which fluid circuit is parametrized - saves time and avoids errors

Characteristics	2K COMFORT with two fluid circuits
Mixing accuracy	+/-1%
Mixing ratio	0.1:1-50:1
Material pressure	Max. 325 bar
A components	Max. 10 per fluid circuit
B components	Max. 5 per fluid circuit
C components	Max. 5 per fluid circuit



1: ee			2
A : B		1.00	:1
Pot life	0	100	min
	0	100	min
Menu -	Act book	PC	



J. Wagner GmbH Industrial Solutions D-88677 Markdorf **Tel +49 (0) 7544 505 - 0** Fax +49 (0) 7544 505 - 1200

J. Wagner AG Industrial Solutions CH-9450 Altstätten/SG Tel +41 (0) 71 7572211 Fax +41 (0) 71 7572323

